

USE, MAINTENANCE AND CARE GUIDE

Initial use:

It is advised not use the floor covering before the glue has hardened completely. During the drying time of the glue indoor conditions have to remain constant. It is absolutely necessary cover the floor immediately after its installation to prevent soiling and damage.

After 12hours start initial cleaning

After 24hours start simple traffic

After 48hours charging with furniture

Note for use and maintenance.

Bondeck has a 5-year commercial wear warranty based on its careful and correct maintenance, but it's not warranted for use in outdoor locations when fully exposed to sunlight. The choice of color and pattern influences the maintenance requirements, as does the layout of entrances and staircases.

Furniture must be fitted with pads of stainless steel, Teflon or similar with no sharp edges. (This is required by all kinds of wall to wall carpeting), so it will not hurt the carpet if moving the furniture. Rubber materials (e.g. car tires) can affect the color of t in case of long-term contact. It is therefore advisable to provide special protection in case of frequent contact with rubber materials. If castor chairs are use it is recommended to provide hard castors.

The Bondeck can be used for stairs, but it is better to use slip stopper or mold to protect it. If Bondeck carpet is laid near entrances, it is important to provide a water and dirt collection system.

The material must be inspected before installation. Do not install flooring with visible defects! Any defects shall be reported to the place of purchase as soon as possible. If the material is deemed defective, we will replace it. Our liability is limited to the replacement of defective material only. Manufacturer is not responsible for cost of removal or reinstallation.

With rolls, depending on the area your waste is between 5 and 10%. This is only a practical rule of thumb and serves as a guideline only. Do not forget to order a small additional quantity to serve as back-up stock for future replacements due to stains, dirt and wear.

Damaged small area can almost invisibly be repaired by cutting out the damaged area and replacing it with spare qty.

We expressively waive any liability pertaining to the above presented ideas, suggestions, guidelines and recommendations for maintaining Bondeck flooring, installation and maintenance methods and practices may vary from country to country. Please always consult your local flooring contractor.

Cleaning:

1. Cleaning after installation (Initial cleaning):

After laying: Construction dust (sand, gypsum,) is very abrasive. It should be removed to avoid the danger of creating premature walking lanes. After vacuum cleaning the whole surface is wet cleaned with an injection extraction machine.

Bondeck products are strong and durable with correct maintenance (please find the sheet below) they will last long.

2. For daily maintenance (routine cleaning)

Just wring dry mop the floor with clean and warm water and vacuum cleaning, for a periodic cleaning, please get help from professional cleaning company. Any stains, please remove immediately, otherwise, the stains will penetrate into the floor/wall covering. You can remove



Occasionally you can use acetone, citrus, Pine-Sol, strongly alkaline cleaning agents, scouring powder or strong solvents, but using more will damage the floor. Please try to use cleaning agent PH value around 7-8 often. Rinse and mop with at least one additional clean water rinse after applying detergent, as detergent residue will attract soil if not properly rinsed. Finally use the Comb hair dryer.



	STAIN	REMOVAL PROCEDURES
1	Acid	Neutralize with ammonia
2	Adhesive tape	Harden with ice, rub off with fingers
3	Alcoholic Beverages	Rinse with cold water, immediately followed by white vinegar, then rinse with cold water again
4	Alkali	Neutralize with vinegar
5	Blood, catsup	Rinse in cold water, then dilute ammonia, sponge with detergent and water, then rinse thoroughly
6	Butter	Rinse with hot water
7	Chewing Gum	Apply ice, rinse with cold water, then sponge with Perchloroethylene (spot remover)
8	Chocolate	Rinse with cold water, sponge with bleach

9	Coffee	Rinse with cold water, sponge with detergent and water
10	Egg	Rinse with cold water, sponge with detergent and water
11	Fruits, berries	If fresh, pour boiling water through stain; if stubborn bleach with hypochlorite or hydrogen peroxide
12	Grass	Sponge with alcohol, then detergent and water
13	Ice Cream	Sponge with Perchloroethylene (spot remover)
14	Iodine	Sponge with alcohol
15	Ink (Pen)	If fresh, sponge with detergent and water. If dried, sponge with bleach, then oxalic acid (spot remover), and then scrub with detergent and water
16	Ink (Ballpoint)	Scrub with detergent and water, then rinse. For stubborn stains, use petroleum jelly, then sponge with Perchloroethylene (spot remover). Some
17	Iron Rust	Sponge with oxalic acid (spot remover), rinse well; or, spread with salt, moisten with lemon juice, then place in the sun
18	Lipstick, wax,	Sponge with alcohol or Perchloroethylene (spot remover)
19	Mildew	Sponge with bleach, followed by water rinse
20	Milk or Cream	Sponge with Perchloroethylene (spot remover)
21	Mustard	Apply warm glycerin, wash with sudsy water and Hydrosulfite bleach
22	Oil	Scrub with detergent and water, sponge with Perchloroethylene (spot remover)
24	Perspiration	Sponge with peroxide and ammonia, rinse with water.
25	Sugar	Sponge with hot water
26	Tar	Moisten with Perchloroethylene (spot remover), scrape off, then sponge residue with same solvent
27	Tea	Scrub with borax solution and rinse, or keep stain moist with lemon juice, then expose to the sun for a day or two
28	Asphalt	Neutral cleaning agent or cleaner's naphtha, a scouring pad may be used
29	Floor adhesive	Adhesive wash or methylated spirit, a scouring pad may be used, Dry carefully with a cotton cloth.
30	Shoe heel marks	Neutral cleaning agent or cleaner's naphtha, a scouring pad may be used
31	Vomit, excrements, urine	Neutral cleaning agent or cleaner's naphtha, a scouring pad may be used

4: Stains removal suggestion sheet

Please remove the stain while they are its liquid state, our flooring will not absorb liquid but after if the liquid stays longer, it will penetrate into the flooring and hen it dries the stain left on the material won't be easy to remove.